

WHAT IS CLAIMED IS:

1. A method of manufacturing an organic EL element, comprising the steps of:  
forming pixel electrodes on a transparent substrate;  
forming on said pixel electrodes by patterning at least one luminescent layer having a certain color and made of an organic compound; and  
forming a counter electrode opposing the pixel electrodes, wherein the formation of the luminescent layer is performed by means of an ink-jet method.
2. The method of manufacturing an organic EL element as claimed in claim 1, wherein the organic compound is a polymer organic compound.
3. The method of manufacturing an organic EL element as claimed in claim 2, wherein the polymer organic compound is a hole injection and transfer type material.
4. The method of manufacturing an organic EL element as claimed in claim 2 or 3, wherein the polymer organic compound is a polyparaphenylene vinylene or its derivative or a copolymer which contains at least either one of these compounds.
5. The method of manufacturing an organic EL element as claimed in any one of claims 1 to 4, wherein said at least one luminescent layer comprises three luminescent layers having different three colors, and at least two luminescent layers in the three luminescent layers are formed by patterning by means of an ink-jet method.
6. The method of manufacturing an organic EL element as claimed in claim 5, wherein said three colors include red, green and blue, and the red luminescent layer and the green luminescent layer are formed by patterning by means of an ink-jet method.
7. The method of manufacturing an organic EL element as claimed



polymer organic compound is a hole injection and transfer type material.

16. The organic EL element as claimed in claim 14 or 15, wherein the polymer organic compound is a polyparaphenylene vinylene or its derivative or a copolymer which contains at least either one of these compounds.

17. The organic EL element as claimed in any one of claims 13 to 16, wherein said at least one luminescent layer comprises three luminescent layers having different three colors, and at least two luminescent layers in the three luminescent layers are formed by patterning by means of an ink-jet method.

18. The organic EL element as claimed in claim 17, wherein said three colors include red, green and blue, and the red luminescent layer and the green luminescent layer are patterned by means of an ink-jet method.

19. The organic EL element as claimed in any one of claims 13 to 18, wherein the blue luminescent layer is formed by a vacuum deposition method.

20. The organic EL element as claimed in claim 19, wherein the blue luminescent layer is made of an electron injection and transfer type material.

21. The organic EL element as claimed in any one of claims 13 to 20, wherein said at least one luminescent layer is laminated with an electron injection and transfer type material.

22. The organic EL element as claimed in any one of claims 13 to 31, further comprising a protective film formed on the counter electrode.

23. The organic EL element as claimed in any one of claims 13 to

0901097 07401  
2007/07/26

22, wherein said pixel electrodes are transparent pixel electrodes.

24. An organic EL display device comprising the organic EL element as claimed in any one of claims 13 to 23.

Handwritten notes and a large handwritten 'B' are present. The notes include:  
Add 80  
Add cu  
Add 11

09001097 074001